





TECHNOLOGY HIGHLIGHTS:

- Standards compliant options

 NFC Forum Tag Type 2
 RAIN UHF RFID
- Label reels may be programmed and printed using standard equipment
- Each tag guaranteed to work
- Versions for on- or off-metal use

EFFICIENTLY TAG LARGE QUANTITIES OF METALLIC ASSETS TO ENABLE POWERFUL RFID APPLICATIONS

- Effortless integration Simply apply tags to metallic assets.
- Ready adoption Interoperable with NFC Forum and RAIN UHF RFID compliant devices.
- Enhanced effectiveness Faster, more accurate than QR-codes or text transactions.

HID Global on-metal Inlays & Labels are small, thin self-adhesive NFC or RAIN® UHF tags for on-metal use. These white PET labels are only 1.2 mm thin and may be encoded and printed in standard label printers to apply logos, bar-codes, QR codes or text. Their flexible special shielding allows application on flat or curved metallic objects like liquid containers, laptops, pipes or machinery.

HID Global on-metal Labels come in five different form factors to suit various applications in an optimal size to performance ratio. NFC labels are NFC Tag Type 2 compliant and my be used with any NFC compatible phone or device. RAIN UHF labels are available in FCC (US) or ETSI (EU) variants. All labels are delivered on reels of 500 pcs. for easy processing in a label printer.

For industrial applications, HF and UHF on-metal labels enhance the speed and accuracy of inventory and process management systems. Using RAIN® RFID

technology, each labeled asset can be identified in the supply chain or connected via Internet of Things (IoT), enabling businesses and consumers to identify, locate, authenticate and engage each item. Printable labels for on-metal use are described in a separate datasheet.

HID Global guarantees each individual RFID Inlay & Label tag will perform to specifications. Our quality assurance streamlines processing and encoding to keep your projects on time and on budget.

Printable labels for off-metal use are described in a separate datasheet. For high-security applications, innovative HID Trusted Tag® Services combines cryptographically secure NFC Inlays & Labels with a cloud-based authentication platform, powering frictionless, secure transactions for proof-of-presence, sweepstakes or product authentication. Ask your HID representative to demonstrate the potential of HID Trusted Tag Services.



	Inlays & Labels				
	HF		UHF		
	ON MATERIAL COMM. MOTAL 23 20 11 11 11 11 11 11 11 11 11 11 11 11 11	Martin Marian. Was a state of the state of	ON META OFF LACE. OTHER STATE OF LACE.	HID CONTRACT AND COORSE	ON NOTAL OFF LASTS. SCORE & GOODS OF
Base Model Number	6E3M30	6E3M45	6K0M11 (EU) 6K0M12 (US) 6F9M11 (EU) UCODE 7XM 6F9M12 (US) UCODE 7XM	6KOM71 (EU) 6KOM72 (US)	6KOM61 (EU) 6KOM62 (US)
ELECTRONIC		'	,		
Operating Frequency	13.56 MHz		869 MHz (EU) / 915 MHz (US)		
Chip Type	NTAG 213		UCODE 8		
Memory	144 byte	EEPROM	96 bit EPC + 32 bit user memory or 128 bit EPC (UCODE 7XM : 2048 bit user memory)		
JHF Reading Distance on Metal 2 W reader ERP, free space	Up to 16 ft (5 m)				
PHYSICAL					
Dimensions	ø 1.2 x 0.03 in (30 x 0.8 mm)	1.8 x 1.8 x 0.03 in (45 x 45 x 0.8 mm)	3.9 x 1.7 x 0.04 in (100 x 43 x 1 mm)	4.2 x 0.7 x 0.04 in (107 x 19 x 1 mm)	2.4 x 0.9 x 0.05 in (60 x 24 x 1.2 mm)
Mounting Method	Self-adhesive / optional: Acrylic glue				
Affixes To	Metal surfaces				
Housing Material	PET (front), printable with resin ribbon				
Weight	0.07 oz (2 g) 0.16 oz (4.5 g)		0.04 oz (1.25 g)		0.03 oz (1 g)
Color	White				
CHEMICAL AND MECHANICAL RESISTANCE					
Water	IP68, 68° F (20° C), 3.3 ft (1 m) × 24h				
Environmental Test Conditions	68° F (20° C), 100 h				
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]				
Shock	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]				
THERMAL					
Storage	-4° to +158° F (-20° to +70° C)				
Operating	-4° to +158° F (-20° to +70° C)				
OTHER					
Standards	ISO/IEC 14443A, NI	FC Forum Tag Type 2	EPC Global Class 1 Gen 2, ISO 18000-6C		
Options	Custom printing and encoding Alternative UCODE 7 chip as long as supplies last. Custom printing and encoding				
Box Size	500 pcs. / roll				
Warranty	1 Year				





hidglobal.com

North America: +1 512 776 9000 Toll Free: 1 800 237 7769 Europe, Middle East, Africa: +44 1440 714 850 Asia Pacific: +852 3160 9800 Latin America: +52 55 5081 1650

© 2019 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design and HID Trusted Tag are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

2019-09-11-hid-rfid-il-inlays-labels-om-ds-en PLT-03513

